

Get More With the I-Core

FEATURES	ICC	I-CORE
Number of Stations	8 to 32	6 to 30
Programmable Rain Delay	7 days	180 days
Independent Programs	4	4
Start Times per Program	8	Up to 16 (D)
Max Station Run Time	12 hrs	12 hrs
Seasonal Adjustment	10% to 150% global	0% to 300% by program
Delay Between Stations (Maximum)	10 hrs	9 hrs
Simultaneous Program Operation	Program D can run concurrent with A, B, or C	Any two programs
Multiple Sensor Inputs	1	Up to 3
Modularity	✓	✓
One Touch Manual Start/Advance	✓	✓
Hunter Quick Check™	✓	✓
Non-volatile Memory	✓	✓
Manual Cycle	✓	✓
One Touch Test Program	✓	✓
Automatic Short Circuit Protection	✓	✓
Pump/Master Valve Programmable by Station	✓	✓
Remote Compatible	✓	✓
Weather-based Adjustment	✓	✓
Dual Voltage Transformer (120/240 VAC)	✓	✓
Cycle and Soak	✓	✓
Easy Retrieve™ Memory		✓
Seasonal Adjustment (Monthly)		✓
Seasonal Adjustment (by Solar Sync)		✓
Sensor Programmable by Zone		✓
Sensor Programmable by Program		✓
Total Run Time Calculator		✓
Large Backlit Graphics Display		✓
No Water Window		✓
Real Time Flow Monitoring/Totaling		✓
Factory Installed SmartPort®		✓
Internal Battery for backup Timekeeping		✓
Multiple Language Programming		✓
Diagnostic Status Indicator		Station/flow/sensor
Cabinet Material Options	Plastic or metal	Plastic or metal
Pedestal Options	Plastic or metal	Plastic or metal

With I-Core, Hunter has redefined “the best”. An upgrade to the full-featured I-Core means easier usability, easier installation, and easier programming. Great new features include a total run time calculator, no water window, and real time flow monitoring. This changes everything.

For more information on the I-CORE Controller visit the Hunter website at: www.hunterindustries.com

